

BATTERYcharge PRO 30A



Developed by professionals – Made for professionals


The OSRAM BATTERYcharge PRO 30A is a professional, intelligent battery charger suitable for a wide range of battery types for 12V and 24V vehicles. Ideal for use when different vehicles and even entire fleets need to be maintained, especially in professional workshops or showrooms. By selecting different battery types and charging levels, the user can set the specific charge required for the different battery types. The BATTERYcharge PRO 30A can deliver variable charging currents up to a maximum of 30A. This is possible for lead-acid batteries as well as lithium batteries (AGM, GEL, STD, EFB, LFP, LiFePO4) and start/stop batteries. Variable charging rates of 5A/10A/20A/30A can also provide flexible slow or fast charging to meet the individual requirements of each user. An integrated test function additionally enables diagnosis of the battery and alternator. OSRAM's professional battery charger with integrated LCD screen runs through an 8-stage charge cycle for lithium batteries and a 9-stage charge cycle for all other batteries to restore and optimize battery performance and improve charge retention. With its light weight, the professional charger from OSRAM is easy to carry and transport around the workshop. In addition, OSRAM provides a 2-year guarantee on this product*

Technical data

Electrical data

Charge Rate (Up to)	30 A
Maintainance Charge (up to)	30 A
Max battery capacity	300 Ah
Min battery capacity	14 Ah

Dimensions & weight



Length	230.0 mm
Width	220 mm
Height	80.0 mm

Additional product data

Recommended to Use With	Motorcycle, Car, Truck, Van, Boat
Stages: Lead, AGM, EFB	9
Stages: Lithium	8
Battery Connection	Crocodile Clamps

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	03-06-2022
Primary Article Identifier	4052899629073
Declaration No. in SCIP database	In work

Product datasheet




Detail

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899629073	Smart Charge Pro 30A	Folding carton box 1	288 mm x 256 mm x 94 mm	6.92 dm ³	2823.00 g
4052899629127	Smart Charge Pro 30A	Shipping carton box 4	531 mm x 306 mm x 222 mm	36.07 dm ³	12092.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction BATTERYcharge PRO

Application advice:
For more detailed application information and graphics please see product datasheet and user instruction.

*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

